

USB To CANFD Series Products

User Mannual

		
<p>SavvyCAN-FD-X2 USB To Dual Channel CANFD</p>	<p>SavvyCAN-FD-C USB To CANFD Cable</p>	<p>SavvyCAN-FD-mPCI USB To Dual Channel CANFD with mini pcie interface (usb2.0 bus)</p>

Date	Revision	Description
2023/01/01	V1.0	First Released
2025/7/19	V1.0	ADD Chapter4, Chapter5

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

Document Catalogue

- Document Catalogue2
- 1 Introduction3
 - 1.1 Product Series.....3
 - 1.2 Product Features.....3
- 2 Hardware Description.....4
 - 2.1 SavvyCAN-FD-X24
 - Specification.....4
 - Pins Out Description5
 - LED Indication6
 - 2.2 SAVVYCAN-FD-C7
 - Specification.....7
 - Pins Out Description8
 - LED Indication9
 - 2.3 SavvyCAN-FD-mPCI9
 - Specification.....10
 - Pins Out Description11
 - LED Indication12
 - Design Reference13
- 3 Connection16
 - 3.1 Enable/Disable Build In 120Ω Term Resistor16
 - 3.2 SavvyCAN-FD-X2/SAVVYCAN-FD-C Connection17
 - 3.3 SavvyCAN-FD-mPCI Connection Figure.....18
- 4 Software.....18
 - 4.1 Description:18
 - 4.2 Software Guide19
 - 4.2.1 How to Use On Windows19
 - 4.2.2 How to Use On Linux19
 - 4.2.3 How to Use On Mac Os.....19
 - 4.2.4 Internal 120Ω Termination Resistor19
 - 4.2.5 CUSTOM Nominal/Data Bit Rate.....20
 - 4.2.6 CAN FD Protocol20
 - 4.2.7 Third Party Software20
- 5 Technic Support.....20

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

1 Introduction

1.1 Product Series

Product Name	CAN Version	Bitrate	Isolation	Max Rate	Interface	Time Stamp
SavvyCAN-FD-X2	CAN2.0A/B CANFD 1.0	12Mbit/s	2500V	15000fps/s	USB 2*DSUB 9PIN	1us
SavvyCAN-FD-mPCI	CAN2.0A/B CANFD 1.0	12Mbit/s	2500V	15000fps/s	MINIPCI (USB Bus)	1us
SavvyCAN-FD-C	CAN2.0A/B CANFD 1.0	12Mbit/s	2500V	15000fps/s	1.5M USB Cable 1*D-Sub 9PIN	1us

The new CAN FD standard (CAN with Flexible Data rate) is primarily characterized by higher bandwidth for data transfer.

The maximum of 64 data bytes per CAN FD frame (instead of 8 so far) can be transmitted with bit rates up to 12 Mbit/s.

1.2 Product Features

- 1 True High-speed USB 2.0 Compatible with CAN specifications 2.0A/2.0B/FD;
- 2 CAN FD support for ISO and Non-ISO standard support software switch;
- 3 CAN FD bit rates data field (64 bytes max.) from 25 kbit/s up to 12Mbit/s;
- 4 Class CAN bit rates data field from 25 kbit/s up to 1 Mbit/s;
- 5 Time stamp Resolution Up to 1 μ s;
- 6 Each CAN FD Signal &Power Separately Isolated Up to 2500 Volts against USB;
- 7 Bus load measurements including error frames and overload frames on physical bus;
- 8 Induced error generation for incoming and outgoing CAN messages;

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

2Hardware Description

2.1 SavvyCAN-FD-X2

The SavvyCAN-FD-X2 is a plug and play high speed USB2.0 to CANFD adapter enables the connection of dual channel CANFD networks to a computer via USB. Each CAN FD channel is separately isolated against USB with a maximum of 2500V.




Specification

Connector	
CANFD	Dual Channel 9PIN D-SUB Connectors
USB	USB plug type A (Computer) USB plug type B (Devicie)

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

CAN Features	
Protocols	CAN 2.0A (standard format) CAN 2.0B (extended format) CAN FD ISO 11898-1:2015 CAN FD non-ISO
CAN bit rates	25 kbit/s up to 1 Mbit/s
CANFD bit rates	25 kbit/s up to 12Mbit/s
USB ESD	IEC 61000-4-2 Level 4 +25 kV (contact discharge) +30 kV (air-gap discharge)
Galvanic isolation	Signal & Power Separately Isolated by 2500 Volts against USB IEC 61000-4-2 Contact IEC 61000-4-2 Air ISO 10605 150 pF / 2 k2 Contact ISO 10605 330 pF 1 2 k2 Contact
Micro controller	180MHZ Cortex-M4 MCU
Timestamp resolution	1 μ s
Built In 120 Ω Termination Resistor	Enable/Disable Through Software
Others	
Temperature	-40° ~ 85°
PCBA Size (L * W * H)	84x80x28 mm
Weight	190g

Pins Out Description


CAN1		PIN OUT Description	
		1	NC
		2	CANL bus line (dominant low)
		3	CAN_GND
		4	NC
		5	NC
		6	NC
		7	CANH bus line (dominant high)
		8	NC
		9	NC

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

CAN0 (Normal)		PIN OUT Description	
		1	NC
		2	CANL bus line (dominant low)
		3	CAN_GND
		4	NC
		5	NC
		6	NC
		7	CANH bus line (dominant high)
		8	NC
		9	NC

Note1: Not connect GND do not affect normal communication, if cable with shielding suggest connect to GND;

LED Indication



When plug SavvyCAN-FD-X2 device to Computer All lights are flashing for one second. Then TERM LED And LINK LED turns to be green.

Led Name	Description
Power LED Indicator	Power Up And Driver Installed LINK LED turns to be blinking.
CAN1 LED Indicator	TX LED Blinking, Sending Data; RX LED Blinking, Receiving Data; TERM LED Green,120Ω Activated;
CAN0 LED Indicator	TX LED Blinking, Sending Data; RX LED Blinking, Receiving Data; TERM LED Green,120Ω Activated;
www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

2.2 SAVVYCAN-FD-C

The SAVVYCAN-FD-C is a plug and play high speed USB2.0 to CANFD converter comes with 1.2m high quality Cable enables the connection of one channel CANFD networks to a computer via USB. CANFD is isolated protection against USB 2500V.




Specification

Connector	
CANFD	9PIN D-SUB Connectors
USB Cable	1.2M High Quality USB Cable with type A
CAN Features	

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com


Protocols	CAN 2.0A (standard format) CAN 2.0B (extended format) CAN FD ISO 11898-1:2015 CAN FD non-ISO
CAN bit rates	25 kbit/s up to 1 Mbit/s
CANFD bit rates	25 kbit/s up to 12Mbit/s
USB ESD	IEC 61000-4-2 Level 4 +25 kV (contact discharge) +30 kV (air-gap discharge)
Galvanic isolation	Signal & Power Separately Isolated by 2500 Volts against USB IEC 61000-4-2 Contact IEC 61000-4-2 Air ISO 10605 150 pF / 2 k2 Contact ISO 10605 330 pF 1 2 k2 Contact
Micro controller	180MHZ Cortex-M4 MCU
Timestamp resolution	1 μ s
Built In 120 Ω Termination Resistor	Disable/Enable Through Software
Others	
Temperature	-40° ~ 85°

Pins Out Description

	1	NC
	2	CAN-L
	3	GND
	4	NC
	5	NC
	6	NC
	7	CAN-H
	8	NC
	9	NC

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

LED Indication




Led Name	LED Status	Description
RXD	Blinking	Receiving Data
TXD	Blinking	Sending Data
TER	Blue Led On	Build In 120Ω Term Resistor Enable;
LINK	Blinking	Power Up and Driver Installed.
	Blue Led On	Power Up Driver Not Installed.

2.3 SavvyCAN-FD-mPCI

The SavvyCAN-FD-mPCI is a plug and play high speed USB2.0 to CANFD CAN Card. CAN FD each channel is separately isolated against USB with a maximum of 2500V.

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com




Specification


Connector	
Dual Channel CANFD	2X3PIN 1mm Connector
Mini PCIE USB	USB BUS
CAN Features	
Protocols	CAN 2.0A (standard format) CAN 2.0B (extended format) CAN FD ISO 11898-1:2015 CAN FD non-ISO
CAN bit rates	25 kbit/s up to 1 Mbit/s
CANFD bit rates	25 kbit/s up to 12Mbit/s
USB ESD	IEC 61000-4-2 Level 4 +25 kV (contact discharge) +30 kV (air-gap discharge)
Galvanic isolation	Signal & Power Separately Isolated by 2500 Volts against USB IEC 61000-4-2 Contact IEC 61000-4-2 Air ISO 10605 150 pF / 2 k2 Contact ISO 10605 330 pF 1 2 k2 Contact
Micro controller	180MHZ Cortex-M4 MCU
Timestamp resolution	1 μ s
Built In 120 Ω Termination Resistor	Activated/Deactivated Through Software
www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

Others	
Temperature	-40° ~ 85°
PCBA Size (L * W * H)	84x80x28 mm
Weight	191 g


Pins Out Description



www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com



LED Indication



www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com


	Description	Indication
A	Power&Driver LED	Blinking, Driver install and Power Up
B	CAN0 120Ω Term	On, CAN0 Term Enable; Off, CAN0 Term Disable
C	CAN1 120Ω Term	On, CAN1 Term Enable; Off, CAN1 Term Disable
D	CAN0 Receive	Blinking, CAN0 Receiving Data;
E	CAN0 Send	Blinking, CAN0 Sending Data;
F	CAN1 Receive	Blinking, CAN1 Receiving Data;
G	CAN1 Send	Blinking, CAN0 Receiving Data;

Design Reference

3PIN Connector Board End

Vendor: HDGC1002WR-S-3P

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com




HDGC 深圳市华德共创科技有限公司
Shenzhen Huade co-create Technology Co.,LTD
TEL: 0755-27129737 FAX: 0755-29940187

-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参数表		TITLE: SH1.0针座卧贴	
X.X	±0.30	X.X*	±3°
X.XX	±0.30	X.XX*	±2°
X.XXX	±0.10	X.XXX*	±1°
APPD: 核准: 谢亮	CHECK: 校对: 王建业	DATE: 2020-12-12	SCALE: 1:1
PART NO: HDGC1002WR-S-XP		UNIT: mm	CODE NUMBER: A070
DRAW: 绘图: 黄艳兰		DATE: 2020-12-12	

Design End

Vendor: HDGC1002H-5P


www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com



MINIPCIE Connector

Vendor: Lotes, AAA-PCI-049-K01

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com



3 Connection

3.1 Enable/Disable Build In 120Ω Term Resistor


Products comes enable build in 120Ω term resistor in default.

If you need external connection of 120Ω termination resistor please refer to below method:

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/quick-start-guide#id-1-5-internal-120o-termination-resistor>

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

3.2 SawyCAN-FD-X2/SAVVYCAN-FD-C Connection





Notes:

<p>Note: Remove jumper When build in 120Ω termination resistor Enable.</p>	<p>Note: Add jumper When build in 120Ω termination resistor Disable.</p>

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

3.3 SavvyCAN-FD-mPCI Connection Figure



4 Software

4.1 Description:

This device works on Windws, Linux, Mac Os.

4.1.1 Windows:

- **SavvyCAN-FD-Version**

Pibiger Release FD version SavvyCAN Software, you can download from below link:

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd>

4.1.2 Linux:

- CAN-UTILS/C/Python On Linux
- Open Source SavvyCAN Compiler Method

4.1.3 MacOs

- Open Source SavvyCAN Compiler Method

4.2 Software Guide

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/hardware-manual>

4.2.1 How to Use On Windows

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/quick-start-guide#id-1-2-how-to-use-on-windows>

4.2.2 How to Use On Linux

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/quick-start-guide#id-1-3-how-to-use-on-linux>

4.2.3 How to Use On Mac Os

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/quick-start-guide#id-1-4-how-to-use-on-mac-os>

4.2.4 Internal 120Ω Termination Resistor

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/quick-start-guide#id-1-5-internal-120o-termination-resistor>

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com

4.2.5 CUSTOM Nominal/Data Bit Rate

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/quick-start-guide#id-1-6-custom-nominal-data-bit-rate>

4.2.6 CAN FD Protocol

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/can-fd-protocol>

4.2.7 Third Party Software

<https://docs.pibiger-tech.com/home/usb-to-can-fd-series/savvycanfd/third-party-software-support>

5 Technic Support

sales@pibiger-tech.com;
support@pibiger-tech.com;

www.pibiger-tech.com	docs.pibiger-tech.com
sales@pibiger-tech.com	support@pibiger-tech.com